



# ***STOPPING LANDFILL METHANE EMISSIONS***

***LIFE BEYOND 1.5 DEGREES: HARD TRUTHS AND SOLUTIONS***

PLANNING AND CONSERVATION LEAGUE'S 2024 CALIFORNIA  
ENVIRONMENTAL ASSEMBLY      JANUARY 27, 2024

Ramin Yazdani, Ph.D., P.E.  
University of California at Davis  
[ryazdani@ucdavis.edu](mailto:ryazdani@ucdavis.edu)

**UC DAVIS**  
AIR QUALITY  
RESEARCH CENTER

# AGENDA

Introduction

Current technologies


Landfill basics

Potential opportunities

Summary

# U.S. METHANE EMISSIONS

- MSW Landfills (15%)
- Natural gas & petroleum systems (30%)
- Manure Management (9%)




SOURCE: U.S. EPA

PAUL HORN / Inside Climate News


# U.S. & CALIFORNIA LANDFILLS

- Per 2021 Inventory Report, U.S. landfills released an **estimated 122.6 million metric tons of carbon dioxide equivalent (MMTCO<sub>2</sub>e)** of methane into the atmosphere
- MSW landfills contributed 103.7 MMTCO<sub>2</sub>e (14.3 percent of total U.S. methane emissions) while industrial landfills contributed the remaining 18.9 MMTCO<sub>2</sub>e (2.6 percent of total)

- California Landfills Estimated GHG Emissions (Data used from recent Carbon Mapper Satellite Methane Surveys)
- Assumption: 30,000 to 48,000 kg of CH<sub>4</sub> per hour continuously emitted  
7.8 to 12.5 MMTCO<sub>2</sub>e per year  
6% to 10% of total CO<sub>2</sub>e released in U.S. from landfills



# CONVERSION TECHNOLOGIES AND PRODUCTS



Source: Renewable Energy from Waste Technologies and Projects, GBB, Inc. Dec. 3, 2013 Presentation

# MASS BURN WASTE-TO-ENERGY FACILITIES NOT IN CALIFORNIA



North Broward County, FL - Wheelabrator



Alexandria/Arlington, VA - Covanta



Springfield, MA - Covanta



Baltimore, MD - Wheelabrator

Source: Renewable Energy from Waste Technologies and Projects, GBB, Inc. Dec. 3, 2013 Presentation

# CALIFORNIA WASTE TO ENERGY FACILITIES

California has been moving away from incineration as a disposal option. In 2022, Gov. Gavin Newsom [signed a law](#) that ended jurisdictions' ability to count incineration as a means of diverting waste from landfills under California AB 939.

## Covanta Stanislaus

- Modesto, CA, began operation in 1989
- 800 TPD
- 22.5 MW sold to Pacific Gas and Electric



## Commerce Refuse-to-Energy

- Commerce City, CA, began operation in 1987
- Owned/operated by Los Angeles County Sanitation District
- 360 TPD
- 10 MW sold to Southern California Edison


## Southeast Resource Recovery

- Long Beach, CA, began operation in 1988
- Owned by City of Long Beach and LA County Sanitation District and operated by Covanta
- 1,380 TPD
- 36 MW sold to Southern CA Edison



**Stops operation by June 2024**

# EXAMPLE: SIERRA ENERGY FASTOX GASIFICATION



Source: <https://sierraenergy.com/>



— WHAT IS THE BEST OPTION  
FOR CALIFORNIA?

STOP LANDFILLING?

TECHNOLOGY,  
PERMITTING, AND COST?

# PROBLEM SOLVING PROCESS

- COLLECT DATA & USE
- Identify problem
- Identify Goal
- Identify Solution
- Implement Solution
- Monitor & Evaluate
- Make Decision





# OCCAM'S RAZOR


- William of Ockham, a 14th-century English philosopher and theologian
- “problem-solving principle that recommends searching for explanations constructed with the smallest possible set of elements.”
- paraphrased as **"other things being equal, simpler explanations are generally better than more complex ones"**

# LANDFILL BASICS

- How is it designed?
- How is constructed?
- How is operated?
- How is landfill gas emissions controlled?
- How long is it monitored and managed?


## SANITARY LANDFILL

Source: Copyright 2006 Brooks Cole- Thomson




# LANDFILL BASICS

- Daily waste filling activity
- Daily cover
- Intermediate cover
- Final cover
- Methane gas recovery system



# WASTE DECOMPOSITION PROCESS

- Initial adjustment (Phase I) Aerobic
- Transition (Phase II)-Aerobic
- Acid formation (Phase III)-days after filling-Anaerobic
- Methane fermentation (Phase IV) – starts within weeks after filling
- Final maturation and stabilization (Phase V)- decades



**CAN WE DO BETTER TO  
REDUCE LANDFILL GHG  
EMISSIONS? —**

# LFG COLLECTION EFFICIENCIES

AVAILABLE AND EMERGING TECHNOLOGIES  
FOR REDUCING GREENHOUSE GAS EMISSIONS  
FROM MUNICIPAL SOLID WASTE LANDFILLS

**Table 2. LFG Collection Efficiencies for Various Cover Materials**

Type of Landfill Cover Material	Gas Collection Efficiency
Operating cell (no final cover)	35%
Temporary cover	65%
Clay final cover	85%
Geomembrane final cover	90%



# ACTIVE WASTE FILLING (OPERATING CELL)

## CURRENT METHOD

- A minimum of 6 inches of compacted earthen material or alternative cover material is used at end of each day
- Active waste filling area has no active gas collection during filling
- No monitoring or control of methane emissions is required in the active areas:
  - no gas collection system is typically installed until later years
  - gas collection in the waste filling areas could result in overpulling and potential landfill fire if not continuously monitored

## OPTIMUM METHOD

- Waste could be covered with less permeable material and thicker layer of soil to reduce emissions
- Active waste filling areas could have an active gas collection during waste filling
  - Horizontal or vertical gas collection system can be installed
  - Horizontal or vertical gas collection system can be adjusted continuously by an automated system to prevent potential landfill fire and overpulling

# INTERMEDIATE COVER (TEMP. COVER)

## CURRENT METHOD

- Intermediate cover is compacted earthen material of at least 12 inches placed on the surface of a fill where no additional solid waste will be deposited within 180 days
- This area may be in active filling area for several years with no gas collection
- The active filling areas of the landfill are not subject to methane emissions monitoring due to safety concerns
- Steep slopes of the landfill are not subject to emissions monitoring due to safety concerns

## OPTIMUM METHOD

- Require geomembrane barrier for intermediate cover with a gas collection system below geomembrane
- Set a time limit that an area would be operated without gas collection (3 months)
- Require horizontal or vertical gas collection system to be installed
- Require gas collection using an automated system to minimize emissions and potential landfill fire
- Use robotic or drones to monitoring emissions in active areas and steep slopes

# FINAL COVER (CLAY OR GEOMEMBRANE)

## CURRENT METHOD

- A geomembrane barrier or clay final caps can be used, depending on bottom liner design and when the landfill was constructed
- Clay caps are weak in tension and can easily crack and allow gases escape and liquids into the landfill over time
- Construct clay caps on side slopes can crack over time and allow gases to escape out and liquids enter the landfill
- Infiltration of liquids after closure can generate more emissions and leachate

## OPTIMUM METHOD

- Require geomembrane barrier instead of clay final cap
- Reduces landfill gas emissions and infiltration of liquids




# GAS COLLECTION SYSTEM

## CURRENT METHOD

- By regulations landfill gas wells must be adjusted once per month to control emissions
- Landfill gas wells are sensitive to atmospheric pressures changes that happen within 24 hrs
- Gas volume can change significantly while gas collection wells are set for a constant flow rate which will results in landfill gas overpulling or underpulling

## OPTIMUM METHOD

- Require gas wells to be adjusted automatically every hour to reduce fugitive emissions from underpulling of gas



**Figure 6.** Nitrogen concentration in the gas collection well with control system off (left) and on (right) as a function of changes in barometric pressure during a 12-h period.

# GAS COLLECTION SYSTEM

**Table 3. LFG Collection Efficiencies in the GHG Reporting Rule**

Description	Gas Collection Efficiency
Area without active gas collection, regardless of cover type	0%
Area with daily soil cover and active gas collection	60%
Area with an intermediate soil cover, or a final soil cover not meeting the criteria below to achieve 95% efficiency, and active gas collection	75%
Area with a final soil cover of 3 feet or thicker of clay and/or geomembrane cover system and active gas collection	95%



Office of Air and Radiation

June 2011

AVAILABLE AND EMERGING TECHNOLOGIES  
FOR REDUCING GREENHOUSE GAS EMISSIONS  
FROM MUNICIPAL SOLID WASTE LANDFILLS


Gas collection efficiencies are site specific and can change significantly depending on field condition and landfill operation

# SUMMARY

Changes in landfill operation that are not required by current regulations can result in immediate and significant reduction in fugitive GHG emissions. They can potentially qualify for voluntary carbon credit to fund the additional costs:

- 1) Early landfill gas collection system to collect more methane
- 2) Geomembrane intermediate and final cover (where not required)
- 3) Automated landfill gas collection system to increase the overall gas collection efficiency

Continue to develop better waste management technologies to eliminate landfills and utilize waste as resources



**THANK YOU**

